
TEMPORARY TRAFFIC CONTROL TYPICAL APPLICATION



NOTES:


IF THE LEAD WORK VEHICLE IS TRAVELING AT THE POSTED SPEED LIMIT OR WITHIN 15 MPH OF IT, THEN NO BACK UP VEHICLE IS NECESSARY.

IN URBAN AREAS THE DISTANCE MAINTAINED BETWEEN VEHICLES MAY BE DECREASED AS NEEDED.

IF ONLY ONE ARROW PANEL IS AVAILABLE IT SHALL OPERATE IN ARROW MODE. EXCEPT A WORK VEHICLE ON THE SHOULDER NEED ONLY DISPLAY THE ARROW PANEL IN THE "CAUTION" MODE.

TMA MAY BE USED ON WORK VEHICLE, IF PROTECTION VEHICLE IS NOT AVAILABLE.

KEY:



 ∞

ARROW PANEL

沖


APPROVED VEHICLE SAFETY LIGHT

Û

DIRECTION OF TRAFFIC

X

TRUCK MOUNTED ATTENUATOR (TMA)



APPROVED CATEGORY CODE ITEMS APPROVED

DIRECTOR - OFFICE OF TRAFFIC AND SAFETY

APPROVAL • SHA REVISIONS HIGHWAY ADMINISTRATION

APPROVAL 8-20-03 APPROVAL 9-23-03

REVISED REVISED

REVISED REVISED

REVISED REVISED

REVISED REVISED

Maryland Department of Transportation STATE HIGHWAY ADMINISTRATION

STANDARDS FOR HIGHWAYS AND INCIDENTAL STRUCTURES

MOBILE OPERATIONS
DIVIDED UNCON. OR EXP-FREEWAY
ALL SPEEDS/O-15 MIN., AND MOVING SLOW

STANDARD NO.

MD 104.04-17